

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 November 2004 (18.11.2004)

PCT

(10) International Publication Number
WO 2004/099571 A1

(51) International Patent Classification⁷: **E21D 21/00.**
E21F 17/02

OBERG, Fredrik [SE/SE]; Restalundsvägen 75, S-702 16 Örebro (SE).

(21) International Application Number:
PCT/SE2004/000732

(74) Agent: **EHRNER & DELMAR PATENTBYRÅ AB**;
P.O. Box 10316, S-100 55 Stockholm (SE).

(22) International Filing Date: 12 May 2004 (12.05.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0301374-5 12 May 2003 (12.05.2003) SE

(71) Applicant (for all designated States except US): **ATLAS COPCO ROCK DRILLS AB** [SE/SE]; Patent, S-70 191 Örebro (SE).


(72) Inventors; and

(75) Inventors/Applicants (for US only): **KANFLOD, Morgan** [SE/SE]; Rimmaguvägen 92, S-705 92 Örebro (SE).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: EXPANDABLE ROCK BOLT AND ROCK BOLTING SYSTEM



(57) Abstract: The present invention is related to a rock bolt (7), expandable by means of a pressure media, for insertion into a borehole. The expandable bolt (7) comprises a connection unit (8) with means (11) for detachable interaction with an expansion means (10) for expansion of the rock bolt (7), as well as with a suspension element (16). The connection unit is designed with such external dimensions so that it may be inserted into the borehole. The invention also relates to such a rock bolting system.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

EXPANDABLE ROCK BOLT AND ROCK BOLTING SYSTEM

Technical field

The present invention is related to expandable rock bolts for use as suspension attachments.

5 Background of the invention

In tunneling and in mines there is often a need for suspending different devices used in the work, for example ventilators, drilling equipment and the like. Additionally, in mines and in tunneling one often uses platforms in order to transport
10 excavated material and other material. These platforms are hung up in the roof of the tunnel or mine, which for example may be done by attaching a beam in the roof and then fastening the platform to the beam.

In order to fasten such devices, for example a service
15 platform, to the roof, bolts of different types may be used. Often one uses expandable bolts, so called swelling bolts where the bolt comprises a tube, the interior of which is pressurized by means of a pressure means, such as a high pressure fluid, and thereby expands. An example of such an
20 expandable bolt is showed in the Swedish patent nr. 7902129-1. The expansion bolts may be used with a special coupling, that is fastened to the expansion bolt. The platform, or the devices that one wishes to suspend in the roof, is then fastened in these couplings.

25 A disadvantage with using these bolts as suspension devices is that they, together with the special suspension coupling, protrude substantially from the roof of the tunnel, and must therefore be cut and/or covered by a thick layer of rendering concrete. This is a costly and time-consuming operation and it

would be desirable to be able to minimize it. This bolt with suspension device may not be ranked as supporting of rock in the safety estimates.

Summary of the invention

5 It is an object of the present invention to provide a rock bolt that solves the above-mentioned problems. More specifically, it is an object of the present invention to provide an improved rock bolt for suspension, which entails minimized stress concentrations in the bolt. Another object of
10 the present invention is to provide a suspension device that simplifies the work when moving into a rock.

These and other objects are achieved in accordance with the present invention by an expandable rock bolt as defined in claim 1.

15 In accordance with the present invention the above mentioned objects are achieved by providing a expandable rock bolt, that can be expanded by means of a pressure media, with a connection unit including means for interaction with means for expanding the rock bolt as well as suspension elements. The
20 connection unit is further designed with such exterior dimensions that it may be inserted into a borehole. Thereby a suspension device is provided that gives a smaller protrusion from the rock, and that provides a better strength.

In accordance with a preferred embodiment, the connection unit
25 comprises a connection sleeve fastened to the rock bolt. Thereby a practical and easy to use connection of the suspension elements and expansion means, respectively, is provided. This connection sleeve may be inserted into the borehole and thereby gives a minimal protrusion from the rock

into the tunnel being covered, which results in a faster and more efficient tunneling work.

In accordance with another preferred embodiment the connection sleeve may be welded to the rock bolt, which gives a more safe and at the same time economical and practical attachment of the connection sleeve to the rock bolt.

In accordance with another preferred embodiment the connection unit's connection sleeve comprises an organ, for example a flange, against which a rock plate may abut. This gives the rock bolt according to the present invention rock supporting qualities, whereby the rock bolt combines two important and useful functions, namely supporting of rock and suspension, in one and the same rock bolt. The rock plate may further be chosen as appropriate and depending on the requirements, and may for example comprise a regular flat rock plate or e.g. a domed rock bolt. In accordance with this aspect of the invention the expandable rock bolt may thus be used both as rock support and as a suspension device. Thereby the total cost for providing suspension devices and rock support may be decreased, giving an economical solution.

In accordance with another preferred embodiment the connection unit comprises a supporting sleeve, surrounding at least parts of the seat of the connection unit. Thereby the rock bolt is prevented from being exposed to bending moment due to the fact that the bolt rests against the wall of the hole.

In accordance with another preferred embodiment two rock bolts may be joined and thereby provide a longer rock bolt. The rock bolt in accordance with the present invention may alternatively be used only as the outermost part, protruding from the rock, whereby regular on the market existing likewise

or otherwise expandable rock bolts, without a connection unit for suspension and plate, may be used farthest in, in the borehole.

5 In accordance with another preferred embodiment the suspension element may comprise one of the following: mounting lug, a single hook, a double hook, a catch or a combination thereof. Great flexibility is thereby provided, and the suspension element may be adapted as required.

10 The present invention also relates to a rock bolting system comprising an expandable rock bolt as above, and expansion nipple and suspension element, whereby advantages, corresponding to the above described, are achieved.

15 Further advantages are achieved by different aspects of the invention and will become clear by the following detailed description.

Brief description of the drawings

Figure 1 shows a rock bolt in accordance with the invention.

20 Figure 2 shows the rock bolt of figure 1 provided with a detachable expansion nipple in accordance with the present invention.

Figure 3 shows the rock bolt of figure 1, where the detachable expansion nipple has been replaced with a mounting lug.

25 Figures 4a and 4b show a second embodiment of a rock bolt provided with a detachable expansion nipple and mounting lug, respectively, in accordance with the present invention.

Figure 5 shows two rock bolts in accordance with the present invention that has been joined.

Detailed description of preferred embodiments

As was described above there is often a need for suspending various devices in a mine or in a tunneling work. In rock drilling supporting of rock of some kind is needed, for example rock bolts, cables or other elements, in order to strengthen and stabilize the rock and thereby making the rock self-supporting. As was described in the introductory part there are expandable, tubular rock bolts that may be used for this purpose, see for example the Swedish patents no. 427 764 and 443 398.

The present invention provides an improved rock bolt, which may also be provided with a suspension device giving a minimal protrusion, and that at the same time provides a way to combine these two needs existing in a rock drilling environment, for example in a mine, in one and the same rock bolt.

With reference now to figure 1, a rock bolt 7 in accordance with the present invention is shown. The by a pressure media expandable rock bolt 7 comprises a connection unit for connection both of an expansion means 10 (see figure 2) and for connection of a suspension element 16 (see figure 3). The connection unit preferable comprises a connection sleeve 8 with a seat comprising internal means 11 for reception both of the expansion organ 10 for expanding the rock bolt 7 and of a suspension element 16. The internal means 11 of the seat may for example comprise threads, whereby the expansion means 10 and the suspension element 16, respectively, may be screwed on to the rock bolt 7. Alternatively, as is shown in the figures 4a and 4b, the connection sleeve 8 may instead comprise external threads for interaction with the expansion means 10 and suspension element 16, respectively. This must however be

done without substantially lengthen the protrusion of the rock bolt from the rock, for example so that a sleeve like part of the expansion means 10 and the suspension means 16 have such dimensions that they may be inserted into the borehole. Other
5 suitable detachable connections are also conceivable.

The connection unit preferably also comprises a supporting sleeve 9, which is fastened to the rock bolt 7. The parts of the connection unit, that is, the connection sleeve 8 and the
10 supporting sleeve 9 in case such is present, may in an alternative embodiment be integrated. Furthermore, the supporting sleeve 9 prevents any undesired angular displacements between the connection sleeve 8 and the rest of the rock bolt 7 thanks to the fact that the sleeve supports
against the wall of the hole.

15 In figure 2 the expansion means 10 is shown in the form of an expansion nipple, but in other embodiments the expansion means 10 may for example be a simple, straight tube or a hollow cable. The function of the expansion means 10 is to allow expansion of the rock bolt 7, and thereby anchorage of the
20 rock bolt 7 in the rock 12. Expansion requires only that the expansion means 10 comprises some kind of hollow body, through which for example water may be fed in under high pressure, whereby the rock bolt 7 expands to abutment against the borehole. An expansion nipple is advantageous in that the
25 pressurization may then be performed by means of a radial injection tube, whereby a manual pressurization is facilitated.

The expansion means 10 preferably fits into an ordinary standard chuck for rock bolt used in rock bolting, and a
30 specially designed chuck is thus not needed for the rock bolt 7 in accordance with the present invention.

In the shown embodiment, the connection sleeve 8 comprises a flange 13 against which a rock plate 14 abuts. Means other than a flange are also conceivable as support for a rock plate 14. By the fact that a rock plate 14 thus may be used in conjunction with the rock bolt 7, the rock bolt 7 may be used also as supporting of rock, which is not possible with prior art suspension devices. The rock plate 14 may be an ordinary, flat plate or may be domed, as is shown in the figure.

When the rock bolt 7 has been expanded by means of the expansion means 10, which expansion means 10 has been connected to a source of the pressure media, not shown, the expansion means 10 may be unscrewed. This provides a rock bolt giving a small protrusion. It is also possible, if desired, to connect a suspension element 16, see figure 3. The rock bolt 7 may thereby be used as a suspension device for e.g. service platforms and the like. The suspension element 16 is provided with means for interaction with the connection sleeve's 8 internal (or external) means 11, for example screw threads. In figure 3 the suspension element 16 is shown in the form of a mounting lug, but in alternative embodiments the suspension element 16 may comprise any suitable suspension means, for example a single hook, a double hook, a crook or any combination of these. A flexible suspension device, which may be adjusted according to need, is thus provided.

Moreover, the suspension element 16 may be unscrewed and be reused as the tunneling is advancing. This gives at least two advantages. Firstly, the cost for the suspension element 16 is reduced, since it may be used several times. Secondly, the protrusion from the rock is small, whereby the need for cutting bolts after use is eliminated, which otherwise is a time-consuming process. Thereby the procedure is speeded up,

and moreover, the required thickness of the covering with rendering concrete or the like is reduced, which per se again reduces the costs. The installation is further very fast, with only a few, simply assembled parts.

5 As is shown in figure 5 the connection unit may be adjusted so that two and more rock bolts 7', 7'' may be joined together in order to form a long bolt. This may be done in different ways. If one wishes to join together two rock bolts 7', 7'' in accordance with the present invention, an outer rock bolt 7'
10 has to have a through cable with a connection nipple 17, that are joined together with a connection sleeve 8 on an internal rock bolt 7''. Application of a pressure media external to the borehole then entails expansion of both bolts 7' and 7''.

15 The inner part of the rock bolt 7 may alternatively be exchanged to a male mounting that is pieced together with an ordinary expandable rock bolt. The rock bolt 7 in accordance with the present invention is then used only as the outermost part, protruding from the rock, while regular jointed expandable rock drills are used farthest in, in the rock 12.

Claims

1. A rock bolt expandable by means of a pressure media for insertion in a borehole and including a connection unit characterized in that the connection unit comprises means (11) for detachable interaction with a expansion means (10) for expansion of the rock bolt (7), as well as with a suspension element (16) connectable to the rock bolt, and in that the connection unit is designed with such external dimensions so that it may be inserted into the borehole.
2. Expandable rock bolt as claimed in claim 1, characterized in that the connection unit comprises a connection sleeve (8) fastened to the rock bolt (7).
3. Expandable rock bolt as claimed in claim 2, characterized in that the connection sleeve (8) comprises means such as a flange (13), against which a rock plate (14) may abut.
4. Expandable rock bolt as claimed in any of claims 1-3, characterized in that the connection unit is fastened to the rock bolt (7) by welding.
5. Expandable rock bolt as claimed in any of the preceding claims, characterized in that the expansion means (10) comprises a nipple that may be inserted into the connection unit.
6. Expandable rock bolt as claimed in any of the preceding claims, characterized in that the connection unit comprises a supporting sleeve (9), surrounding at least parts of the seat of the connection unit.
7. Expandable rock bolt as claimed in any of the preceding claims, characterized in that the rock bolt (7') present a

through canal and a connection nipple (17) on a internal part for connection to a second rock bolt (7'').

8. Expandable rock bolt as claimed in any of the preceding claims, characterized in that the suspension element (16)
5 comprises one of the following: a mounting lug, a single hook, a double hook, a crook or a combination thereof.

9. A rock bolting system comprising an expandable rock bolt as claimed in any of claims 1-8, and an expansion means (10) and a suspension element (16) for interaction with the connection
10 unit of the rock bolt (7).




Fig 1





Fig 2






Fig. 4a




Fig. 4b




Fig. 5

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/000732

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: E21D 21/00, E21F 17/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: E21D, E21F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3651651 A (L. TRIPLET), 28 March 1972 (28.03.1972), figures 3,4, abstract --	1-9
A	US 5997219 A (D. KRZYSZTALOWICZ ET AL), 7 December 1999 (07.12.1999), figures 1,3, abstract --	1-9
A	SE 443398 B (ATLAS COPCO AB NACKA), 24 February 1986 (24.02.1986), figures 1,4, abstract --	1-9
A	SE 427764 B (ATLAS COPCO AB, NACKA), 2 May 1983 (02.05.1983), figure 1, abstract --	1-9

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

5 August 2004

Date of mailing of the international search report

06-08-2004

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Björn Lindkvist / MRo
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

03/07/2004

International application No.

PCT/SE 2004/000732

US	3651651	A	28/03/1972	NONE		
<hr/>						
US	5997219	A	07/12/1999	AU	2237097 A	10/09/1997
				CA	2246996 A	28/08/1997
				EP	0882173 A	09/12/1998
				JP	2000504800 T	18/04/2000
				NO	975258 A	17/11/1997
				SE	504605 C	17/03/1997
				SE	9600640 A	17/03/1997
				WO	9731177 A	28/08/1997
				SE	508558 C	12/10/1998
				SE	9700085 A	16/07/1998
<hr/>						
SE	443398	B	24/02/1986	AT	10664 T	15/12/1984
				AU	545968 B	08/08/1985
				AU	7505481 A	18/03/1982
				BR	8105714 A	25/05/1982
				CA	1180909 A	15/01/1985
				DE	3167630 D	00/00/0000
				EP	0047727 A,B	17/03/1982
				FI	75400 B,C	29/02/1988
				FI	812763 A	09/03/1982
				IN	153175 A	09/06/1984
				JP	1582190 C	11/10/1990
				JP	2005238 B	01/02/1990
				JP	57077798 A	15/05/1982
				NO	159201 B,C	29/08/1988
				NO	812997 A	09/03/1982
				PL	134505 B	31/08/1985
				PL	232949 A	15/03/1982
				SE	8105344 A	09/03/1982
				US	4423986 A	03/01/1984
				ZA	8106176 A	29/09/1982
<hr/>						

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

03/07/2004

PCT/SE 2004/000732

SE	427764	B	02/05/1983	AT	7943	T	15/06/1984
				AU	542263	B	14/02/1985
				AU	5624680	A	11/09/1980
				CA	1233037	A,C	23/02/1988
				CA	1245486	A	29/11/1988
				DE	3068155	D	00/00/0000
				EP	0016742	A,B	01/10/1980
				FI	72576	B,C	27/02/1987
				FI	800717	A	10/09/1980
				JP	1577229	C	24/08/1990
				JP	2000520	B	08/01/1990
				JP	55123000	A	22/09/1980
				NO	157348	B,C	23/11/1987
				NO	800606	A	10/09/1980
				PL	125315	B	30/04/1983
				PL	222538	A	01/12/1980
				SE	7902129	A	10/09/1980
				SU	1144625	A	07/03/1985
				US	4459067	A	10/07/1984
				US	4509889	A	09/04/1985
				US	4634317	A	06/01/1987
				ZA	8001380	A	28/01/1981
